



Aluminium Slewing Crane

Technical Data

- Suspension point at the bolt of the Trolley 3,000 mm.
- For indoor and outdoor use.
- Rotates trough 360°.
- With lock detent / brake unit (Concept: similar to drum brake mechanism).
- Height of Slewing Crane:
 - total height 3,380 mm
 - column height 3,000 mm
- Boom arm:
 - total length 2,000 mm
- The Aluminium Slewing Crane is demountable into 5 pieces:
 - column
 - boom arm
 - support profile, incl. brake unit
 - brace
 - trolley, incl. manual trolley direction bandand can be easily mounted by at least two persons.
- The Aluminium Slewing Crane can be mounted respectively pegged directly onto the ground or flange-mounted onto the bracket (item no. 23010).



load capacity 250 kg
weight 130 kg

Item No. 5600253020

load capacity 500 kg
weight 130 kg

Item No. 5600503020

Item No. 23010

Bracket for Aluminium Slewing Crane

Description

- Suitable for Aluminium Slewing Crane with 250 kg and 500 kg.
- For indoor and outdoor use.
- Flange-mounted onto Aluminium Slewing Crane
- For fixation onto wall e.g. concrete.



Picture: Aluminium Slewing Crane with bracket



Picture: Aluminium Slewing Crane and bracket demounted