



Electric Chain Hoist



for Aluminium Gantry Crane, load capacity 1,000 kg, small, medium

load capacity 1,000 kg
length of chain under load 3 m
overall height 463 mm
weight 33 kg

Item No. 250103

for Aluminium Gantry Crane, load capacity 1,000 kg, high

load capacity 1,000 kg
length of chain under load 4 m
overall height 463 mm
weight 35 kg

Item No. 250104

for Aluminium Gantry Crane, load capacity 1,500 kg, small, medium

load capacity 1,500 kg
length of chain under load 3 m
overall height 570 mm
weight 54 kg

Item No. 250153

for Aluminium Gantry Crane, load capacity 1,500 kg, high

load capacity 1,500 kg
length of chain under load 4 m
overall height 570 mm
weight 57 kg

Item No. 250154

for Aluminium Gantry Crane, load capacity 2,000 kg

load capacity 2,000 kg
length of chain under load 4 m
overall height 570 mm
weight 57 kg

Item No. 250204

for Aluminium Gantry Crane, load capacity 3,000 kg

load capacity 3,000 kg
length of chain under load 4 m
overall height 710 mm
weight 134 kg

Item No. 250304

Description

- version with suspension hook
- manufactured in accordance with EU-Machinery Directive and Equipment Safety Law
- Protection Class EN 60529: IP55
- Suitable for internal and exterior use. The Electric Chain Hoist is „splash-proof“.

- Lifting mechanism:
- ambient temperature rating -20 up to +40° C
 - lifting speed 1.00/4.00 m/min
 - lifting motor power 0.2/0.8 kW
 - duty cycle 20/40% ED
 - galvanised chain
 - fixed mounting

- Electrical:
- direct control
 - operation voltage 400 V
 - control voltage 48V
 - frequency (cycles) 50Hz
 - control unit including control cable
 - control unit protection class IP 55
 - Can also be delivered with radio control. Please contact us.