



Wheel Kit for Aluminium Gantry Crane



Item No. 24001

- For indoor moving and positioning of the Aluminium Gantry Crane without load.
- 4 steel swivel casters
- with integrated wheel and live ring brake
- own weight 70 kg

Attention:

- When using this Wheel Kit together with our Aluminium Gantry Cranes
 - the minimum suspension point at the bolt of the trolley is increased by 400 mm
 - the maximum suspension point at the bolt of the trolley is increased by 200 mm.
- The adjustment range of the Wheel Kit feet is 200 mm.

with heavy-duty polyurethane lining



with super-elastic-solid rubber tyres

Item No. 24002

- For indoor and outdoor moving and positioning of the Aluminium Gantry Crane without load.
- 4 steel swivel casters
- heavy-duty tyres with groove profile
- with integrated wheel and live ring brake
- own weight 80 kg

Description

- Facilitates the moving of the assembled Aluminium Gantry Crane without load.
- The leg and fork construction permits the lateral stands to remain upright when assembling and disassembling.

Attention:

- When using this Wheel Kit together with our Aluminium Gantry Cranes
 - the minimum suspension point at the bolt of the trolley is increased by 440 mm
 - the maximum suspension point at the bolt of the trolley is increased by 240 mm.
- The adjustment range of the Wheel Kit feet is 200 mm.
- The unloaded Aluminium Gantry Crane can easily be moved to the working area.
- The Wheel Kit spares any mounting and dismounting work.
- The spring mounted guide rolls allow the lateral stands to rest directly on the feet when under load.
- The adjustment feet are individually height adjustable.
- 1 Wheel Kit = 4 "forks"